# Contents


1. Introduction ..... 1-1

1.1. Document Organization ..... 1-1

1.2. Typographic Conventions ..... 1-2

2. Basic Concepts ..... 2-1

2.1. Link State Databases and Algorithms ..... 2-1

2.1.1. Maintaining Adjacencies between Routers and their Neighbors ..... 2-2

2.1.2. Synchronizing Link State Information Among Routers ..... 2-2

2.1.3. Determining a Designated Router and Constructing Pseudonodes ..... 2-3

2.1.4. Incorporating Switched Circuits into the Design ..... 2-4

2.1.5. The Circuit Concept in Link State Design ..... 2-5

2.1.6. Example of Link State Database ..... 2-5

2.1.7. Decision Process and Forwarding ..... 2-6

2.1.8. Load-Splitting ..... 2-10

2.2. Reliability Features of NLSP ..... 2-10

2.2.1. Disseminating Updates Reliably ..... 2-10

2.2.2. Operating with Database Overload ..... 2-11

2.2.3. Calculating and Testing Checksums ..... 2-11

2.2.4. Coping with System Bugs ..... 2-11

2.2.5. Implementing Fail-Stop Operation ..... 2-11

2.3. The Criterion Used in Determining Routes ..... 2-12

2.4. Information Useful to Higher Layers ..... 2-12

2.5. Routing Information Protocol ..... 2-13

2.5.1. RIP for Communicating with End Nodes ..... 2-13

2.5.2. RIP for Backward Compatibility ..... 2-14

2.6. Service Advertising Protocol ..... 2-14

2.7. NetBIOS and Packet Type 20 ..... 2-15

2.8. Enhancing NLSP to Hierarchical Routing ..... 2-15

2.9. IPX Addressing and its Relationship to Routing ..... 2-17

2.10. Network Management ..... 2-19

2.11. Capabilities Assumed in the System Environment ..... 2-20

2.11.1. Configuration of Parameters by End Users ..... 2-20

2.11.2. Event Handling ..... 2-21

2.11.3. Characteristics of Links to Support NLSP ..... 2-21
2.11.4. Imposing Jitter on Timed Operations ..... 2-21
2.12. IPX Protocol ..... 2-23
2.12.1. General Processing of Incoming IPX Packets ..... 2-23
2.12.2. IPX Checksum ..... 2-25
2.12.3. IPX Ping Protocol ..... 2-26
2.13. Packet Structures ..... 2-27
2.13.1. IPX Header ..... 2-28
2.13.2. IPX Ping ..... 2-30
3. IPX WAN Version 2 ..... 3-1
3.1. Support of Several Routing Protocols ..... 3-1
3.2. Implementing Media-Dependent Functions ..... 3-2
3.2.1. Operation over PPP ..... 3-2
3.2.2. Operation over X.25 Switched Virtual Circuits ..... 3-2
3.2.3. Operation over X.25 Permanent Virtual Circuits ..... 3-2
3.2.4. Operation over Frame Relay ..... 3-3
3.2.5. Operation over IP Relay ..... 3-3
3.2.6. Operation over other WAN media ..... 3-4
3.3. Outline of the Stages of IW2 Operation ..... 3-4
3.4. IW2 Packets and their Usage ..... 3-4
3.5. Steps of the Initial Negotiation for Router-Router Operation ..... 3-5
3.6. Remaining Steps for the Numbered RIP Routing Type ..... 3-7
3.7. Remaining Steps for the Unnumbered RIP Routing Type ..... 3-8
3.8. Remaining Steps for On-Demand, Static Routing ..... 3-8
3.9. Remaining Steps for the NLSP Routing Type ..... 3-9
3.9.1. Normal IW2 Exchanges for NLSP ..... 3-9
3.9.2. NLSP Configured Values ..... 3-12
3.10. Client-Router Connection ..... 3-13
3.10.1. Agreeing on Master/Slave Roles and Routing Type ..... 3-13
3.10.2. Choosing the Network Number ..... 3-14
3.10.3. Choosing the Node Number ..... 3-14
3.11. Checking and Recovery Features of IW2 ..... 3-15
3.12. Recalibrating Throughput and Delay ..... 3-16
3.13. Forwarding “Type 20” Packets ..... 3-16
3.14. IW2 Database ..... 3-17

3.14.1. Constant Values ..... 3-17
3.14.2. Configured Values ..... 3-17
3.14.3. Dynamic Values ..... 3-17
3.14.4. Dynamic Values per Circuit ..... 3-18
3.15. Packet Structures ..... 3-18
3.15.1. IPX WAN 2 ..... 3-19
4. Adjacencies ..... 4-1
4.1. Maintaining Adjacencies over WANs ..... 4-1
4.1.1. Maintaining WAN Links ..... 4-1
4.1.2. Sending WAN Hello Packets ..... 4-2
4.1.3. Receiving WAN Hello Packets ..... 4-2
4.2. Maintaining Adjacencies over LANs ..... 4-6
4.2.1. Enabling LAN Circuits ..... 4-6
4.2.2. Sending LAN Hello Packets ..... 4-7
4.2.3. Receiving LAN Hello Packets ..... 4-8
4.2.4. Maintaining Existing LAN Adjacencies ..... 4-9
4.2.5. Detecting New LAN Adjacencies and Updating Adjacency States ..... 4-9
4.2.6. Detecting Obsolete LAN Adjacencies ..... 4-10
4.2.7. Designated Router Election ..... 4-10
4.3. Adjacency Database ..... 4-11
4.3.1. Constant Values ..... 4-11
4.3.2. Configured Values of the Local System ..... 4-12
4.3.3. Configured Values per Circuit ..... 4-12
4.3.4. Dynamic Values per Circuit ..... 4-12
4.3.5. Dynamic Values per Adjacency ..... 4-13
4.3.6. NLSP Events ..... 4-13
4.4. Packet Structures ..... 4-14
4.4.1. WAN Hello ..... 4-16
4.4.2. LAN Level 1 Hello ..... 4-18
5. Link State ..... 5-1
5.1. Overview of the Protocol ..... 5-1
5.2. Generating and Checking the LSP Checksum ..... 5-2
5.2.1. Symbols and Conventions ..... 5-2
5.2.2. Generating a Checksum ..... 5-3

5.2.3. Checking a Checksum ..... 5-3
5.2.4. Partial Precomputation ..... 5-4
5.3. The Need for Multiple LSPs ..... 5-4
5.4. Determining Which of Two LSPs is Newer ..... 5-5
5.5. Pseudonodes and Designated Routers ..... 5-6
5.6. Aging Out an LSP and Purging Superseded LSPs ..... 5-7
5.7. Periodic LSP Generation ..... 5-7
5.8. Event-Driven LSP and CSNP Generation ..... 5-8
5.9. Generation of Level 1 Non-Pseudonode LSPs ..... 5-8
5.10. Generation of Level 1 Pseudonode LSPs ..... 5-13
5.11. Preparing to Initiate Transmission ..... 5-14
5.12. Receipt and Propagation of LSPs ..... 5-14
5.12.1. Expired LSP with the Same System ID ..... 5-15
5.12.2. Expired LSP with a Different System ID ..... 5-16
5.12.3. Unexpired LSP with the Same System ID ..... 5-16
5.12.4. Unexpired LSP with a Different System ID ..... 5-16
5.13. Storing a New LSP ..... 5-17
5.14. Receipt of Sequence Number Packets ..... 5-17
5.15. Transmitting the Packets ..... 5-18
5.15.1. Expiration of a Complete SNP Interval ..... 5-19
5.15.2. Expiration of a Partial SNP Interval ..... 5-20
5.15.3. Expiration of Minimum LSP Transmission Interval ..... 5-20
5.15.4. Circuit Pacing to Avoid Circuit Congestion ..... 5-21
5.15.5. Multiple Circuits Connected to the Same LAN ..... 5-21
5.16. Determining the Latest Information ..... 5-22
5.16.1. Operation of Sequence Numbers ..... 5-22
5.16.2. Resolving LSP Confusion ..... 5-22
5.16.3. Synchronizing LSP Expiration ..... 5-23
5.17. Validation of Databases ..... 5-24
5.18. Managing LSP Database Overload ..... 5-24
5.19. Link State Database ..... 5-25
5.19.1. Configured Values ..... 5-25
5.19.2. Configured Values per Circuit ..... 5-26
5.19.3. LSP Database ..... 5-26
5.19.4. NLSP Events ..... 5-26

5.20. Packet Structures ..... 5-27
5.20.1. Level 1 LSP ..... 5-29
5.20.2. Level 1 CSNP ..... 5-33
5.20.3. Level 1 PSNP ..... 5-35
6. Decision Process ..... 6-1
6.1. Running the Decision Process ..... 6-1
6.2. Dijkstra's Algorithm in Pseudocode ..... 6-1
6.3. Load-splitting ..... 6-3
6.4. Information Used and Not Used ..... 6-4
6.5. Products of the Decision Process ..... 6-5
6.6. Routing in the Face of a LAN Partition ..... 6-5
6.7. Routing Outside the Routing Area ..... 6-6
6.7.1. Calculating the Actual Area Address ..... 6-6
6.7.2. Routing to an Exit Router ..... 6-7
6.7.3. Forwarding Data Packets ..... 6-8
6.8. Decision Process Database ..... 6-8
6.8.1. Configured Values ..... 6-8
6.8.2. Dynamic Values ..... 6-8
6.8.3. NLSP Events ..... 6-8
7. RIP and SAP ..... 7-1
7.1. Maintaining RIP and SAP Information ..... 7-2
7.1.1. XRoutes and Services Defined ..... 7-2
7.1.2. Relation to Link State Database of Receiving RIP/SAP ..... 7-3
7.1.3. Relation to Link State Database of Sending RIP/SAP ..... 7-5
7.1.4. XRoutes, NLSP Routes, Services, and the Decision Process ..... 7-6
7.1.5. Building a RIP Route from the Link State Graph ..... 7-7
7.1.6. Aging XRoutes and Services ..... 7-8
7.2. Generating Periodic Updates ..... 7-9
7.3. Split Horizon ..... 7-9
7.4. Generating Triggered Updates ..... 7-10
7.4.1. Changes in XRoutes and Services ..... 7-10
7.4.2. Changes in the Link State Graph ..... 7-11
7.4.3. Circuit Activation and Deactivation ..... 7-11
7.4.4. Router Activation and Deactivation ..... 7-12
7.5. Receiving RIP and SAP Packets ..... 7-13

7.6. Maintaining a Proper Interpacket Gap ..... 7-15
7.7. RIP and SAP Filters ..... 7-15
7.8. RIP/SAP Database ..... 7-16
7.8.1. Configured Values per Circuit ..... 7-16
8. Network Management ..... 8-1
8.1. Managing an NLSP Area ..... 8-1
8.1.1. Examining Error Statistics and Counters ..... 8-1
8.1.2. Using the Graph and the LSP Database to Locate Problems ..... 8-3
8.1.3. Using the Neighbors Table and Statistics to Locate Problems ..... 8-4
8.1.4. RIP and SAP Parameters That Must Be Consistent ..... 8-5
8.2. IPX Network Management Information ..... 8-5
8.2.1. System Group ..... 8-6
8.2.2. Circuit Group ..... 8-6
8.2.3. Forwarding Group ..... 8-6
8.2.4. Services Group ..... 8-7
8.2.5. Traps Group ..... 8-7
8.3. RIP and SAP Network Management Information ..... 8-7
8.3.1. System Group ..... 8-7
8.3.2. Circuit Group ..... 8-8
8.4. NLSP Network Management Information ..... 8-8
8.4.1. System Group ..... 8-8
8.4.2. Circuit Group ..... 8-8
8.4.3. Forwarding Group ..... 8-9
8.4.4. NLSP Neighbors Group ..... 8-9
8.4.5. Translation Group ..... 8-9
8.4.6. Graph Group ..... 8-9
8.4.7. LSP Group ..... 8-10
8.5. MIB Definitions ..... 8-11
8.6. IPX MIB ..... 8-12
8.7. RIP/SAP MIB ..... 8-23
8.8. NLSP MIB ..... 8-27
9. Comparison with IS-IS ..... 9-1
9.1. Terminology in the Specification Document ..... 9-1
9.2. Addressing Issues ..... 9-1

9.3. Routing Issues ..... 9-2
9.4. End Node Support ..... 9-3
9.5. Data-Link Issues ..... 9-3
9.6. System Integrity Issues ..... 9-4
9.7. Packet Format and Framing ..... 9-4
9.8. System Management ..... 9-5
10. LAN Frame Types ..... 10-1
10.1. Universal Address Representation ..... 10-1
10.2. Ethernet 802.2 ..... 10-3
10.3. Ethernet SNAP ..... 10-4
10.4. Ethernet Raw 802.3 ..... 10-4
10.5. Ethernet II ..... 10-4
10.6. Token Ring ..... 10-5
10.7. Token Ring SNAP ..... 10-5
10.8. FDDI ..... 10-6
10.9. FDDI SNAP ..... 10-6
11. References ..... 11-1